



ASSA ABLOY

ASSA ABLOY Entrance Systems Ltd
 Industrial Door and Docking Solutions
 7 Churchill Way .35A Business Park
 Chapeltown Sheffield UK S35 2PY


Tel: +44 (0)114 257 4330
 Fax: +44 (0)114 257 4399



ELEVATION



SECTION



Inside
 PLAN

Contractors Notes:

Contractor to provide a flush fixing face for installation of the door. Jamb and lintels to be flush, plumb in the same plane & clear of projections. Also please take into account all head & side room clearances required to accommodate the door. We remind you that its the clients responsibility to ensure the structure is suitable to accept the weight of the door, components & fixings. If in doubt please engage the services of a structural engineer. Approx Door Weight: **35kg's m²**


Electrical Requirements

A 415v 3 phase pre-wired motor with integral limit switches, low level control panel with panel mounted UP DOWN & STOP buttons and a 5 pin pre-wired plug. Client **must** provide a surface mounted 16 amp 5 pin (3 phases earth & neutral) mains wired female socket within 1 metre of the control panel.

Qty: . Nr As Drawn Ref: .

Operation: Safedrive Type: Non Insulated

Coil: Rev Std Rail: 'L' 'T'



Finish: Powder Coat Galvanised
 Plast Ext Face

Rev	Description	Date
-	-	-

Drawn		DO NOT SCALE!
Date		
Chk'd		Date
Drg No.		Rev