



- FW= Frame width  
Min. 2220 / max. 4400
- FH= Frame height  
Min. 2000 / max. 2500
- X= Distance to avoid finger trap (83-200 mm)
- COW= Clear opening width  
 $COW = (FW - 103 - 2X) / 2$
- COH= Clear opening height  
 $COH = FH - 44$
- CL= Cover length

- State when ordering
- FW=.....mm
  - FH=.....mm
  - X=.....mm
  - COW=.....mm
  - COH=.....mm
  - CL=.....mm

- Surface treatment
- Silver anodized
  - Special anodized.....
  - RAL.....
  - Special powder coating.....

- Glass
- 8 mm laminated glass
  - 10 mm laminated glass
  - 12 mm laminated glass
  - 8 mm tempered glass
  - 10 mm tempered glass

- Lock
- Floor lock Euro 1-way
  - Floor lock Euro 2-way

Scale 1:5

Customer: \_\_\_\_\_

Door id: \_\_\_\_\_

Project No: \_\_\_\_\_

EntreMatic ref: \_\_\_\_\_

Date: \_\_\_\_\_

Sign: \_\_\_\_\_

**Profile system  
EMPS-SB with EMSL  
4 Panel wall mounted**

**ENTRE MATIC**

5      833051