



**STATE WHEN ORDERING**

FW/CL = ..... mm  
 FH = ..... mm  
 COW = ..... mm  
 COH = ..... mm

**Surface treatment**

Silver anodized  
 Special anodized .....  
 RAL .....  
 Special powder coating .....

**Options see layers:**

- Handle outside, 950 mm height
- Top rail 175 (if door mounted sensor)
- Midrail 70, MH = ..... mm
- Midrail 150, MH = ..... mm
- Bottom rail 201
- Lock LELME
- SW100, PUSH
- SW200, PUSH

**Glass, see layers:**

- 6 mm laminated glass
- 6 mm tempered glass
- 8 mm laminated glass
- 8 mm tempered glass
- 22 mm insulated glass

① Cable inlet

Be aware of the operator opening direction, see arrows on drive unit.  
 SW100 must have dip switch setting as for PULL arm.

Customer: \_\_\_\_\_  
 Door id: \_\_\_\_\_  
 Project No: \_\_\_\_\_

Ref: \_\_\_\_\_  
 Date: \_\_\_\_\_  
 Sign: \_\_\_\_\_

Automatic Swing Door system  
 ASSA ABLOY Balance-L  
 Arm system **PUSH**

**ASSA ABLOY**  
 11.0 1011810-en